

HCF Series Cable Connector



Technical Data

- Thread specification: International metric standard
- Material: Nylon 66
- Working temp.: -40°C~+100°C
- Max temp. in short time: +120°C.
- Installation: Standard threaded hole
- Colour: Black & gray

Order Information

Cabel range (mm)	Thread external diameter (mm)	Panel hole (mm)	Thread length (mm)	Spanner size A&F	Reference Black	Gray
7.6-4.6	12	12.5	8.5	18/19	HCFMG12IP68B	HCFMG12IP68W
10-6	16	16.5	15	22/22	HCFMG16IP68B	HCFMG16IP68W
14-9	20	20.5	15	27/27	HCFMG20IP68B	HCFMG20IP68W
18-13	25	25.5	15	33/33	HCFMG25IP68B	HCFMG25IP68W
25-18	32	33	15	41/41	HCFMG32IP68B	HCFMG32IP68W
30-24	40	41	20	50/50	HCFMG40IP68B	HCFMG40IP68W
41-30	50	51	22	62/62	HCFMG50IP68B	HCFMG50IP68W
51-40	63	64	25	75/75	HCFMG63IP68B	HCFMG63IP68W
7-3.5	7	12.5	8	17/19	---	HCFPG7IP54W
8-4.5	9	15.2	8.5	22/19	---	HCFPG9IP54W
10.5-6	11	18.6	9	24/22	---	HCFPG11IP54W
12.5-7.5	13.5	20.4	9.6	27/24	---	HCFPG135IP54W
14-8.5	16	22.5	10	30/27	---	HCFPG16IP54W
18-12.5	21	28.3	12	36/33	---	HCFPG21IP54W
25-18	29	37	15	46/41	---	HCFPG29IP54W
30-23	36	47	15	57/50	---	HCFPG36IP54W
39-30	42	54	15.5	64/62	---	HCFPG42IP54W
45-35	48	59.3	15.5	70/65	---	HCFPG48IP54W