

# HJXF Metal Enclosure

Standard: EN60529



## Function

HJXF Metal Enclosure provide:

- Control, monitoring, measurement and protection for the electric power loops and main power controlling equipment.

## Order Information

Type	Thickness of iron charge(mm)	Dimension(mm)									Lock	Reference
		Overall			Installation		Mounting					
		H	W	D	H1	B1	H6	B6	Thick			
HJXF—2520 / 14 IP43 Improved	1.0	250	200	140	290	150	170	158	1.0	1	HJXF252014B	
HJXF—3025 / 14 IP43 Improved	1.0	300	250	140	340	200	220	208	1.0	1	HJXF302514B	
HJXF—3025 / 18 IP43 Improved	1.0	300	250	180	340	200	220	208	1.0	1	HJXF302518B	
HJXF—3030 / 14 IP43 Improved	1.0	300	300	140	340	250	220	258	1.0	1	HJXF303014B	
HJXF—3030 / 18 IP43 Improved	1.0	300	300	200	340	250	220	258	1.0	1	HJXF303018B	
HJXF—4030 / 14 IP43 Improved	1.0	400	300	140	440	250	320	258	1.0	1	HJXF403014B	
HJXF—4030 / 20 IP43 Improved	1.0	400	300	200	440	250	320	258	1.0	1	HJXF403020B	
HJXF—5040 / 14 IP43 Improved	1.0	500	400	250	540	350	420	358	1.0	2	HJXF504014B	
HJXF—5040 / 20 IP43 Improved	1.0	500	400	140	540	350	420	358	1.0	2	HJXF504020B	
HJXF—5040 / 25 IP43 Improved	1.0	500	400	200	540	350	420	358	1.0	2	HJXF504025B	
HJXF—6040 / 14 IP43 Improved	1.2	600	400	250	640	350	520	358	1.2	2	HJXF604014B	
HJXF—6040 / 20 IP43 Improved	1.2	600	400	140	640	350	520	358	1.2	2	HJXF604020B	
HJXF—6040 / 25 IP43 Improved	1.2	600	400	200	640	350	520	358	1.2	2	HJXF604025B	
HJXF—6050 / 14 IP43 Improved	1.2	600	500	250	640	450	520	458	1.2	2	HJXF605014B	
HJXF—6050 / 20 IP43 Improved	1.2	600	500	140	640	450	520	458	1.2	2	HJXF605020B	
HJXF—6050 / 25 IP43 Improved	1.2	600	500	160	640	450	520	458	1.2	2	HJXF605025B	
HJXF—7050 / 16 IP43 Improved	1.2	700	500	200	740	450	620	458	1.2	2	HJXF705016B	
HJXF—7050 / 20 IP43 Improved	1.2	700	500	250	740	450	620	458	1.2	2	HJXF705020B	
HJXF—7050 / 25 IP43 Improved	1.2	700	500	200	740	450	620	458	1.2	2	HJXF705025B	
HJXF—8060 / 20 IP43 Improved	1.5	800	600	250	840	550	720	558	1.5	2	HJXF806020B	
HJXF—8060 / 25 IP43 Improved	1.5	800	600	250	840	550	720	558	1.5	2	HJXF806025B	
HJXF—10080 / 20 IP43 Improved	1.5	1000	800	200	1040	750	920	758	1.5	2	HJXF1008020B	
HJXF—10080 / 25 IP43 Improved	1.5	1000	800	250	1040	750	920	758	1.5	2	HJXF1008025B	
HJXF—10080 / 30 IP43 Improved	1.5	1000	800	300	1040	750	920	758	1.5	2	HJXF1008030B	

Final Distribution

# HJXF Metal Enclosure

Standard: EN60529

CE

## Technical Data



Type	HJXF IP43 Improved
Protection grade	IP43
Standard:	EN60529
Certificate	CE
Rated voltage	220/400V
Rated insulated voltage	660V
Rated operating current	400A
Withstand current	15kA
Sheet thickness	1.0~1.5mm
Mounting plate thickness	1.0~1.5mm
Hinge	Enhanced
Sealing rubber gasket	Black rubber gasket
Cable gland	bottom only

Final Distribution

## Overall Dimensions

Unit: mm

